

Fig 1


Transmit 201
Receive 202
Tx.dat
Tx.Ctl
Rx.Ctl
Rx.dat
Transmit memory 211
Receive Memory 215
Transport Layer 210
213
Packetizer 212
TX controller
RX controller 217
Depacketizer 216
codes
codes
8
Encoder 221
control symbol generator 223
control symbol identifier 226
Link Layer 220
9
9
9
8
Data Selector 222
Decoder 225
symbols
symbols
9
9
Physical Layer 230
Transmitter 231
Receiver 235
serial symbols
Serial symbols

Fig 2


Physical Layer
230
235
305
304
303
Frame Aligner
Digital PLL
Over sampler
Rx.dat
Receiver
302
clock
PLL
301
231
Transmitter
Tx.dat

Fig 3


Packet
400
Large →
Medium →
Small →
Reserved 1
411
Reserved 2
412
Destination Address
413
Source Address
414
Type
415
Protocol
416
Class-specific control
417
Transaction Index
418
410 header
Payload
420

Fig 4


Payload 510
500
501
502
503
504
505
506
Header
Block 1
Block 2
Block 3
Block 4
Block 5
Block 6
570
address 500a
500
501
502
503
504
Header
Block 1
Block 2
Block 3
Block 4
520
address 500a
531a
531
505
506
Header
Block 5
Block 6
530
address
+4

Fig 5


600
T.1
8 7 6 5 4 3 2 1 0
Packet Memory Before Merge
610
611
612
613
614
T3 Add=25 Blocks=5
T1 Add=4 Blocks=3
T2 Add=50 Blocks=10
T1 Add=0 Blocks=2
Received Packet
630
T1 Add=2 Blocks=2
Packet Memory After Merge
620
611
613
614
T3 Add=25 Blocks=5
T2 Add=50 Blocks=10
T1 Add=0 Blocks=7

F. 8 6


Send Data Packet w/ segmentation
701
wait for a block
702
XOFF
Y
703
wait for XON
N
Send header
704
Send one block
705
706
XOFF
Y
N
707
Next block ready
Y
N
Send CRC
708

Fig 7


Receive Data Packet with Segmentation
801
receive data packet
802
select next data packet in packet memory
803
all data packets already selected
Y
804
add receive packet to packet memory
Done
N
N
selected + received packets contiguous
Y
805
update received header
806
merge blocks into received packet
807
remove selected from packet memory

Fig 8



Sync + packet type

Fig 9A



FIG.10

Fig 9B



Fig. 9C



Fig 10


store packet
retrieve Net packet
1101
1102
N
Y
Control packet
1104
1103
store packet in Data Queue
store packet in Control Queue

Fig 11


Select Packet
1201
Control Queue Empty
N
1202
retrieve packet from control Queue
Y
1203
Data Queue Empty
Y
N
1204
retrieve packet from data Queue
1205
Select next symbol of packet
1206
all symbols already selected
Y
N 1207
Send selected symbol

Fig 12



Fig 13


Send Packet w Preempt
1401
retrieve next packet
1402
retrieve next code of retrieved packet
1403
all codes retrieved
Y
N
1404
transmit retrieved code
1405
Preempt
N
Y
1406
transmit preempt primitive
1405
select next code
1408
all codes already selected
Y
1410
transmit continue primitive
N
1409
transmit retrieved code

Fig 14


Receive Packet
retrieve next symbol
1501
1502
preempt primitive
N
1503
add to packet
Y
1504
save current packet info
1505
Process Preempting Packet
1506
restore saved packet info

Fig 15



Fig 16


Host
Data Store
T2
T1
P4 P3 P2 P1 P2 P1
T1 T2 T1 T2 T2 T2
P2 P4 P1 P3 P2 P1
Preserving Packet Order w/ Transaction
T2 T1 T2 T2 T1 T2
P2 P2 P4 P3 P1 P1
T1
T2
P1 P2 P1 P2 P3 P4
No Packet or Transaction Ordering

Fig 17


Identify Output Link for D.S. Load B
1801
retrieve data packet
1802
has another packet of Xaction been sent
Y
N
1803
1804
identify same output link
identify other output link
Done

Fig 18



Fig 19A



Fig 19B


Handle Error
1921
receive error type information
1922
receive packet id information
1923
Generate error packet
1924
send error packet to host
Done

19C

8b Code	9 bit symbol
0000 0000	101010101
0000 0001	101010100
0000 0010	101010111
⋮	
0101 0101	001010101
⋮	
0111 0110	001110110
0111 0111	100100010
⋮	
1111 1111	110101010

Fig 20



Fig 21A



Fig 21B



Fig 2

Fig 2 C


IDLE
Packet
PRIM
Packet (cont'd)
IDLE
OOB
OOB
negative disparity
positive disparity

Fig 22


Encode Code
2301
Optimize Transitions
2302
Buffer Symbol
2303
complete block or end of packet
N
Y
2304
running disparity = block disparity
N
Y
2305
Insert Block
Provide Symbols to physical layer
2306
Done

Fig 23


Optimize Transitions
2401
receive code
2402
count transitions
2403
number of trasitions <4
N
2404
set qth bit to 0
Y
2405
invert every other bit
2406
set qth bit to 1
2407
symbol is qth bit + code
Done

Fig 24


Invert Block
2501
select 1st symbol of group
2502
inverts every other bit
2503
select next symbol of block
2504
all symbols already selected
Y
Done
N
2505
invert bit of selected symbol

Fig 25


Decode code
2601
Buffer symbol
2602
Primitive
Y
2603
Process Primitive
N
2604
complete block or end of packet
N
Done
Y
2605
1st symbol ODB
Y
06
Undo Block Invasion
N
Select next symbol
2607
2608
all already Selected
Y
Done
N
2609
Undo Optimize Transition
2610
Provide code to transport layer

Fig 26


Undo Block Inversion
2701
Select 1st Symbol
2702
invert alternate bits
2703
select next symbol
2704
all already selected
Y
Done
N
2705
invert all bits

Fig 27


Undo Optimize Transitions
2801
9th bit == 1
N
Y 2802
invert alternate bits
Done

Fig 28


Process Primitive
2901
preempt
Y
2904
Signal Preempt
N
2902
continue
Y
2905
Signal continue
N
2903
idle
Y
2906
Signal Idle
N

Fig 29



Fig 30


Physical Layer
3100
clock
3121
3120
Phase Lock Loop
3123
3123
3122
De-Serializer
Serializer
Serializer
De-Serializer
RxO
TxO
RxN
TxN
3110
3119

Fig 31

Input Queue 3201

Port	R/W	Address	Data
3	R	1000	
4	W	4000	10....1
3	W	1000	111...0
3	R	2000	
	⋮		

Output Queue 3202

Valid	Port	Data
1	3	11...0
0		
0		
1	3	101...1
	⋮	

Fig 32


Access Layer (Receive)
Receive next command
3301
Write
3302
Y
3305
Process Write Command
N
3303
Read
Y
3306
Process Read Command
N
3304
Other
Y
3307
Process other command

Fig 33


Process write command
3401
retrieve target Addies
3402
Configure Switch
3403
read next byte
3404
Done
Done
3405
store address/data in Input Queue
3406
increment address

Fig 34


Access Layer Transmit
3501
receive next byte
3502
Done
3504
end of packet
Done
3503
provide byte to transport Layer

Fig 35


ROW Addr
3630
ROW DEC
3600
3610
Section 0
Section 1
3601
3602
3611
3612
en0
en1
NXm
NXm
3650
Cofig
Port
CR
3604
3614
COL DEC & COL$ 0
COL DEC & COL$ 1
3603
3613
COL Addr
2N

Fig 36



Variable Driver $\begin{cases} RD^{+} \wedge \overline{DataIn} = \text{pull down} \\ RD^{-} \wedge DataIn = \text{pull up} \end{cases}$

Fig 37A



Fig 37B



Fig 38A



Fig 38B



Fig 39A



Fig 39B


Serial storage channel
3N phase clocks
3x over-sample
4011
3N-bit data
4012
PLL
Phase selector
4013
2 bit control
V_{N-1}, V_N
(N+1)-bit
D[0:N]
4010
NULL insert/remover
Local clock
DET_ERR
DET_NULL
N-bit data
RX_DAT[N-1:0]
4020
4000

Fig 4D



Fig 41



Fig 42A



Fig 42B



Fig 42C



Fig. 43



LD = 1, iHF = 0, iPTR = "001000000"

LD = 1, iHF = 1, iPTR = "000000100"

Fig 44



Fig 45



Fig 46



Fig 47A



Fig 47B



Fig 48A



Fig 48B



Fig. 49A



Fig 49B